

EGE KİMYA A.Ş.

HEADQUARTERS

Cendere Yolu No. 16-18
Kağıthane 80350
İSTANBUL / TÜRKİYE
Tel : (0-212) 294 65 67 -74
Fax : (0-212) 294 52 98
e-posta/e-mail : info@egekimya.com

FACTORY

Aşağı Kirazca Mevkii, Nehirkent
ADAPAZARI / TÜRKİYE
Tel : (0-264) 229 32 00 - 09
Fax : (0-264) 229 38 54 -55



TS-EN-ISO-9001

1102

PRODUCT DATA

Definition of the product

Ground coat enamel frit (medium component)

Properties :

Physical state	solid
Shape	flake
Firing temperature (C)	820±10
Melting point/range (C)	500
Bulk density (gr/cm ³)approx.	1.14

Application fields are :

Used in ground coat combination for cover coats, can also be used as a single coat where no chemical resistance is required.

Packaging :

25 kgs.bags craft paper

Expiry data :

Unlimited in dry and clean area

APPLICATION :

Applied on pre-treated enamel quality sheet steel commonly in combination with 1101 and 1103. The percentage in the combination can vary in accordance with the conditions of users.

SAFETY DATA

Hazard Identification :

Inflammable.

Handling and Storage :

Handling : Provide for sufficient ventilation at the working place.

Storage : Keep the product in a clean and dry area.

Transport Information :

ADR Class : Not applicable
RID Class : Not applicable
IMDG Class : Not applicable
IATA Class : Not applicable

