

EGE KİMYA A.Ş.

HEADQUARTERS

Cendere Yolu No. 16-18
Kağıthane 80350
İSTANBUL / TÜRKİYE
Tel : (0-212) 294 65 67 -74
Fax : (0-212) 294 52 98
e-posta/e-mail : info@egekimya.com

FACTORY

Aşağı Kirazca Mevkii, Nehirkent
ADAPAZARI / TÜRKİYE
Tel : (0-264) 229 32 00 - 09
Fax : (0-264) 229 38 54 -55



TS-EN-ISO-9001

1105

PRODUCT DATA

Definition of the product

Direct on brown ground coat enamel frit

Properties :

Physical state	solid
Shape	flake
Firing temperature (C)	800±10
Melting point/range (C)	500
Bulk density (gr/cm ³)approx.	1.26

Application fields are :

Stoves and stove pipes

Packaging :

25 kgs.bags craft paper

Expiry data :

Unlimited in dry and clean area

APPLICATION :

Brown pigment is added to mill composition and it is applied on pre-treated enamel quality sheet steel .

SAFETY DATA

Hazard Identification :

Inflammable.

Handling and Storage :

Handling : Provide for sufficient ventilation at the working place.

Storage : Keep the product in a clean and dry area.

Transport Information :

ADR Class : Not applicable
RID Class : Not applicable
IMDG Class : Not applicable
IATA Class : Not applicable

