

EGE KİMYA A.Ş.

HEADQUARTERS

Cendere Yolu No. 16-18
Kağıthane 80350
İSTANBUL / TÜRKİYE
Tel : (0-212) 294 65 67 -74
Fax : (0-212) 294 52 98
e-posta/e-mail : info@egekimya.com

FACTORY

Aşağı Kirazca Mevkii, Nehirkent
ADAPAZARI / TÜRKİYE
Tel : (0-264) 229 32 00 - 09
Fax : (0-264) 229 38 54 -55



TS-EN-ISO-9001

AI-28

PRODUCT DATA

Definition of the product

Transparent aluminium frit

Properties :

| | |
|---|--------|
| Physical state | solid |
| Shape | powder |
| Firing temperature (C) | 560±10 |
| Melting point/range (C) | 400 |
| Bulk density (gr/cm ³)approx. | 0,75 |

Application fields are :

Household utensils, outsides of hollowware etc.

Packaging :

25 kgs.bags craft paper

Expiry data :

Unlimited in dry and clean area

APPLICATION :

Applied on pre-treated aluminium alloy which is convenient for enamelling.
With addition of coloring pigments in high quantities, nice colors are achieved.

SAFETY DATA

Hazard Identification :

Inflammable.

Handling and Storage :

Handling : Provide for sufficient ventilation at the working place.

Storage : Keep the product in a clean and dry area.

Transport Information :

ADR Class : Not applicable
RID Class : Not applicable
IMDG Class : Not applicable
IATA Class : Not applicable

