

EGE KİMYA A.Ş.

HEADQUARTERS

Cendere Yolu No. 16-18
Kağıthane 80350
İSTANBUL / TÜRKİYE
Tel : (0-212) 294 65 67 -74
Fax : (0-212) 294 52 98
e-posta/e-mail : info@egekimya.com

FACTORY

Aşağı Kirazca Mevkii, Nehirkent
ADAPAZARI / TÜRKİYE
Tel : (0-264) 229 32 00 - 09
Fax : (0-264) 229 38 54 -55



TS-EN-ISO-9001

24029

PRODUCT DATA

Definition of the product

Black pigment Cu-Mn-Cr-Mo
Cas Nr: 68186-91-4*

Properties :

Physical state	solid
Shape	powder
Color	black
Melting point/range C >	1000
Bulk density (gr/cm ³)approx.	1.43

Application fields are :

Used with clear enamels and/or ground coat enamels
in required amounts

Packaging :

25 kgs.bags craft paper

Expiry data :

Unlimited in dry and clean area

APPLICATION :

Used 1-4% in ground coat enamels. At least 2-3% pigment has to be used to get intense color.
In transparent enamels 3-4 % pigment gives intense color.

SAFETY DATA

Hazard Identification :

Inflammable.

Handling and Storage :

Handling : Provide for sufficient ventilation at the working place.

Storage : Keep the product in a clean and dry area.

Transport Information :

ADR Class : Not applicable
RID Class : Not applicable
IMDG Class : Not applicable
IATA Class : Not applicable

