



EGESİL KİMYA A.Ş.

HEADQUARTERS

Cendere Yolu No. 16-18

Kağıthane 80350

ISTANBUL / TURKIYE

Tel : (0-212) 294 65 67 -74

Fax : (0-212) 294 52 98

e-posta/e-mail : info@egekimya.com

FACTORY

Aşağı Kirazca Mevkii, Nehirkent

ADAPAZARI / TURKIYE

Tel : (0-264) 229 32 00 - 09

Fax : (0-264) 229 38 54 -55



TS-EN-ISO-9001

EGESIL BS20 A

PRODUCT DATA

Properties :

Synthetic sodium aluminium silicate. Extender pigment for synthetic as well as emulsion paints.

Physical and chemical properties :

(Typical values)

| | |
|-----------------------------------|---------------|
| Appearance | white -powder |
| Surface Area, (m ² /g) | 85 |
| Volatiles at, (%105 °C) | 6 |
| Ph Value (%5 in water) | 10 |
| Sieve Residue (45µm, %) | 0.05 |
| Luminance Factor | 97 |

Application fields are :

Paint and paper industry.

Packaging :

Kraft bag (laminated)
(25 kg)

Expiry data :

One year from production date.

APPLICATION :

Paint industry use this product due to its hiding power, prevention of TiO₂ agglomeration during dispersion, improves the quality of white paints.

SAFETY DATA

CAS No : 1344-00-9

Hazard Identification :

None known.

Description of dangers:

On the basis of information available to us, this product is not a hazardous substance in the sense of the law on chemicals or the regulations on the hazardous substances in the version which is currently valid.

Handling and Storage :

-Direction for safe handling :

Local ventilation if necessary.

-Directions on fire and explosion safety :

Take precautionary measures against static discharges.

-Storage:

Store in a dry place.

Transport Information :

Dangerous according to the transport regulations:

GGVS/GGVE/RID/ADR/IMDG Code/ ICAO - TI no

